

## SPECIFICATIONS

Thermodynamic cycle	Diesel 4 stroke	
Air Handling	TCA	
Bore x Stroke	millimeters	99 x 110
Total displacement	liters	3.4
Valves per cylinder	number	2
Cooling System	liquid	
Direction of Rotation (viewed facing flywheel)	anti-clockwise	
Compression ratio	18.5:1	
Injection System	-	
EGR	-	

## PERFORMANCES

Rated power [*]	kW (HP) @ rpm	55 (-) @ 2300
Peak torque	Nm (kgm) @ rpm	320 (-) @ -
High idle speed	rpm	2300
Low idle speed	rpm	--
Minimum starting temperature without auxiliaries	°C	25°
Oil and oil filter maintenance interval for replacement	hours	-

## STANDARD CONFIGURATION

Flywheel housing	type	-
Flywheel size	inch	-
Intake manifold location	-	
Exhaust manifold location	-	
Turbocharger	fix geometry / wastegate	
Turbocharger location	front high / right side	
Fan transmission ratio	1.1:1	
Distance between fan - crankshaft centers	millimeters	X=0 Y=296
Fuel filter	number	single cartridge - left side
Fuel prefilter	-	
Fuel Pump	-	
Oil filter	number	single cartridge - left side
Oil sump	sheet steel / central sump	
Oil vapours blow-by circuit	on valve cover	
Oil heat exchanger	incorporated built in the crankcase	
Oil filler	on valve cover	
Alternator	12 V - 90 A with W contact	
Hydraulic steering pump	-	
Wiring harness	sectioning connector on engine wiring for EGR control unit	
Painting color	-	
Starter	12 V - 3 kW	
Maximum torque available from crankshaft pulley	Nm	-
Engine stop device	-	

## WEIGHT AND DIMENSIONS

Dimensions	LxWxH (mm)	753.2 x 589.4 x 896.5
------------	------------	-----------------------

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

## POWER & TORQUE

## NOT INCLUDED IN STANDARD CONFIGURATION

Power Take Off (PTO)	
PTO - transmission ratio	
PTO - maximum available torque	--
Battery - minimum capacity recommended	Ah
Battery - minimum cold cranking capacity recommended	Ah

## LEGEND

Arrangement	Air Handling	Turbocharger	Injection System	Exhaust System
L (in line)	TCA (Turbocharged with aftercooler)	WG (Wastegate)	M (Mechanical)	EGR (Exhaust Gas Recirculation)
V (90° "V" configuration)	TC (Turbocharged)	VGT (Variable Geometry Turbocharger)	ECR (Electronic Common Rail)	SCR (Selective Catalytic Reduction)
	NA (Naturally Aspirated)	TST (Twin Stage Turbocharge)	EUI (Electronic Unit Injector)	
			MPI (Multi Point Injection)	

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



LEGEND

Arrangement	Air Handling	Turbocharger	Injection System	Exhaust System
L (in line)	TCA (Turbocharged with aftercooler)	WG (Wastegate)	M (Mechanical)	EGR (Exhaust Gas Recirculation)
V (90° "V" configuration)	TC (Turbocharged)	VGT (Variable Geometry Turbocharger)	ECR (Electronic Common Rail)	SCR (Selective Catalytic Reduction)
	NA (Naturally Aspirated)	TST (Twin Stage Turbocharge)	EUI (Electronic Unit Injector)	
			MPI (Multi Point Injection)	

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE [WWW.FPTINDUSTRIAL.COM](http://WWW.FPTINDUSTRIAL.COM)

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

